

Project:

Fixture Type:

Location:

Contact:

One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED



Description:

Images:

The simple design of this LED Dome pendant offers complements a wide array of styles from industrial to farmhouse. The 17w LED pendant is 3000K in a Satin Aluminum finish with a painted silver interior. This is an ideal fixture for residential and commercial applications.

Specifications:

- Satin Aluminum (-16) (powder coat paint) •
- Aluminum Construction •
- Satin Aluminum, painted silver inside aluminum shade, White acrylic Diffuser .
- LED Module is replaceable (part # 93053641)
- · Inspired to enhance modern home decor.
- · Complements a wide array of styles from industrial to farmhouse.
- Satin Aluminum finish with a painted silver interior. •
- · Dimmable to 10% with many ELV dimmers
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI. •
- Dimmable to 10% brightness (See Dimming Notes) •
- Canopy covers a standard 4" octagonal recessed outlet box •
- . Mounting strap for outlet box included
- 10 feet of wire supplied .
- ENERGY STAR[®] gualified .

Performance:

Number of Modules	1	Diar Heiş Ove
Input Power	17w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1211/71.2 (LM-82)	Glas Wid Lenş Glas Wid Lenş Heiş
Lumens/LPW (Delivered)	662/40.4 (LM-79)	
CCT	3000 K	
CRI	90+	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 ℃	
Warranty	5 year warranty	
Labels	cCSAus Dry location listed	
	ENERGY STAR [®] qualified	



P5341-1630K9

Dimensions:

ameter: 16" ight: 8-7/8" erall Ht. W/Cord: 129"

ass dth: 16" 1gth: 16" ass 2 dth: 5-13/16" 1gth: 5-13/16" ight: 0-1/2"



One-Light Pendant W/HAL AC LED Module

Ceiling cord mounted • Dry location listed PROGRESS LED

P5341-1630K9

Dimming Notes:

P5341 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.