

Ceiling mounted • Dry location listed **PROGRESS LED**

Description:

This Braden 56 inch, three-blade, hugger-style ceiling fan features clean lines and a design that complements modern interiors. A shatterproof white opal glass shade contains an integrated 18W LED module, offering both form and function with energy and cost-savings benefits. Featuring a larger motor, Braden moves more air than a traditional hugger ceiling fan. A full function remote with batteries is included.

Specifications:

- Architectural Bronze (-129) (painted)
- Steel construction
- White Opal Shatterproof glass Flat Round
- 56" Braden three-blade hugger ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefit
- A white opal, shatterproof shade contains a 18W dimmable, 3000K LED module with 90CRI and 1400 lumens (source)
- Indoor ceiling fan ideal for rooms with low ceiling heights
- Features reversible Medium Cherry and Classic Walnut blades
- Rich Architectural Bronze finish
- Braden features a larger motor and moves more air than a traditional hugger ceiling fan
- Braden hugger fan mounts close to the ceiling only
- A Full function hand held remote control with fan speed control, reverse control and full range light dimming is included and comes with a convenient wall bracket for storage
- Features modern styling for contemporary living spaces
- Reversible motor for year round comfort allows you to choose either a down drafts (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- UL Dry location listed and rated for indoor use
- Limited Lifetime Warranty
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 80" of wire supplied
- Classic Walnut/Medium Cherry reversible blades, plywood construction
- 13 degree blade pitch
- Remote Control With Hand Held Transmitter
- Triple capacitor speed control
- Meets California Title 24 JA8-2016
- Airflow: 4263 CFM*
- Energy consumption: 55 watts (excluding lights)*
- Airflow efficiency: 77 cfm/watt

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1400/77 (LM-82)/
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
Warranty	Limited Lifetime
Labels	cULus Dry location listed Meets California Title 24 JA8-2016

P2588-12930K

Images:



Dimensions:

 Diameter: 56"
 Height: 9-7/8"

 Width: 6"
 Height: 1-5/8"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$10

\$3 | | | \$34

Cost Range of Similar Models (19" – 84")

* Based on 12 cents per kWh and 6.4 hours use per day
 • Your cost depends on rates and use
 • Energy Use: 37 Watts

All estimates based on typical use, excluding lights

Airflow

3,118

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
 • Airflow Efficiency: 85 Cubic Feet Per Minute Per Watt

ftc.gov/energy

P2588-12930K

Dimming Notes:

P2588 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton -AWSMT-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.